


Oil Pattern Distance	39	Reverse Brush Drop	38	Oil Per Board	40 ul
Forward Oil Total	15.32 mL	Reverse Oil Total	6.36 mL	Volume Oil Total	21.68 mL
Tank Configuration	Only A	Tank A Conditioner	N/A	Tank B Conditioner	N/A

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	3	10	111	0.0	2.8	2.8	4440
2	5L	5R	2	10	62	2.8	5.6	2.8	2480
3	7L	7R	2	14	54	5.6	9.5	3.9	2160
4	9L	9R	3	14	69	9.5	15.4	5.9	2760
5	11L	11R	3	18	57	15.4	23.0	7.6	2280
6	13L	13R	2	18	30	23.0	28.1	5.1	1200
7	2L	2R	0	26	0	28.1	39.0	10.9	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	0	39.0	20.0	-19.0	0
2	12L	12R	2	14	34	20.0	16.1	-3.9	1360
3	10L	10R	2	14	42	16.1	12.2	-3.9	1680
4	8L	8R	2	14	50	12.2	8.3	-3.9	2000
5	4L	4R	1	14	33	8.3	6.4	-1.9	1320
6	2L	2R	0	10	0	6.4	0.0	-6.4	0

Cleaner Ratio Main Mix NA Forward
 Cleaner Ratio Back End Mix NA Reverse
 Cleaner Ratio Back End Distance NA Combined
 Buffer RPM: 4 = 720 | 3 = 500 | 2 = 200 | 1 = 50



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside Track:Middle	Middle Track:Middle	Inside Track:Middle	Middle: Inside Track	Middle:Middle Track	Middle:Outside Track
Track Zone Ratio	4.07	1.45	1	1	1.45	4.07

